

RFK-0620 Flake Ice Machine

Models

RFK0620A

RFK0620W



Model **RFK**-0620A Flake Ice Machine on D-420 Bin

Standard Features

- Up to 760 lbs. (345 kgs) daily flake ice production.
- High load maintenance free bearing for enhanced reliability
- Service updates facilitate installation and make cleaning easier.
- Flake ice is perfect for food display, salad bars, and cold therapy/healthcare
- Ice forms around object without bruising and holds objects in place without tipping/spilling.
- Heavy duty stainless stell cabinet resists corrosion.



Specifications

BTU per hour:

Air: 5,200 (average) Water: 2,250 (average) Compressor:

Nominal rating: 1 HP

Refrigerant: R452A

Ice Machine Electric

230/50/1

Minimum circuit ampacity:

7.7 amps (air) 7.1 amps (water)

Maximum fuse size:

15 amps

HACR-type circuit breakers can be used in place of fuses.

Ave Power Consumption:

1,050 W

Ice Shape

Flake ice is small hard bits of ice ideally suited for presentation applications.



Ice shown actual size

Operating Limits:

- Ambient Temperature Range: 50°-110°F (10°-43°C)
- Water Temperature Range 37°-90°F (3°-32°C)
- Water Pressure Ice Maker Water In Min. 14 psi (96.5 kPA) Max. 80 psi (551.6 kPA)
- Condenser Inlet Water In: (water-cooled only)
 Min. 20 psi (137.9 kPA)
 Max. 150 psi (1034.2 kPA)

Water Condenser not for sea water applications.



Welbilt Deutschland GmbH Auf der Weih 11 D - 35745 Herborn, Germany Tel.: +49 27 72 58 050 welbilt.com.de Welbilt Iberia, S.A.U Textil, 6 – Pol.Ind. La Ferreria - 08110 Montcada i Reixac Barcelona, Spain Tel.: +34 902 20 10 69 welbilt.com.es Welbilt UK Ashbourne House, The Guildway, Old Portsmouth Rd, Guildford GU3 1LR, United Kingdom Tel.: +44 1483 464900 www.welbilt.uk




www.manitowocice.com

MANITOWOC[®]



RFK-0620 on D-420 Storage Bin



- (A) Electrical Entrance (2) Options
- B 3/8" F.P.T. Condenser Inlet (water-cooled only)
- © 1/2" M.P.T. Condenser Drain (water-cooled only) ① 1/2" M.P.T. Ice Making Water Drain ⓒ 3/8" F.P.T. Ice Making Water Inlet

- F 3/4" Bin Drain

Space-Saving Designs



RFK-0620 on D-420

76.00" Height 193.00 cm 22.00" Width 55.90 cm 34.00" Depth 86.36 cm


310 lbs. Bin Storage 140.7 kgs

Height includes adjustable bin legs 6.00" to 7.00", (15.24 to 17.78 cm) set at 6.00" (15.24 cm).

Accessories

K-00472 30" D Style Bin Adapter for fitting to D-570 ice bin.

Air Flow Overhead View



Model	Ice Shape	Ice Production 24 Hours Based on Air/Water Temp				Power kWh/100 lbs	Potable Water Usage	Condenser Water at 90/70°F
			0°F Water 0° C Water		0°F Water I° C Water	@ 90°Air/70°F (100 lbs./ Water 45.4 kgs of Ice)		32° Air/21° C Water
RFK0620A	Flake	760 lbs.	345 kgs	540 lbs.	245 kgs	4.74	12 gal./45.4 L	N/A
RFK0620W	Flake	744 lbs.	337 kgs	586 lbs.	266 kgs	3.98	12 gal./45.4 L	70 gal./265 L

Welbilt reserves the right to make changes to the design or specifications without prior notice.

www.manitowocice.com

Installation Note -

Top/sides: 8" (20.32 cm), Back: 5" (12.70 cm).

Minimum installation clearance:

